

# iROBO-30424-51A2

## 3U Industrial Rackmount Computer



## Specifications

### CPU

- Intel® Core™ i3/i5/i7/i9/Pentium/Celeron 12th/13th/14th Generation:

i9-14900	i7-14700	i5-14500	i3-14100	i9-13900	i7-13700	i5-13500	i3-13100
5.8 GHz	5.4 GHz	2.6 GHz	3.5 GHz	5.6 GHz	5.2 GHz	2.5 GHz	3.4 GHz
i9-12900	i7-12700	i5-12500	i3-12100	G6900E	G7400E		
5.1 GHz	4.9 GHz	3.0 GHz	3.3 GHz	3.6 GHz	3.0 GHz		

### Memory

- 4x 288-pin DIMM sockets
- Supports up to 128GB DDR4 3200 MHz, unbuffered, None ECC or ECC

### Chipset

- Intel® W680

### Graphic

- Integrated in CPU Intel® UHD Graphics 770 / 730 / 710  
Support DirectX 12, OpenGL 4.5, OpenCL 2.1, Triple View
- Video ports: HDMI, Display Port, VGA
- DP++ 1.4a: resolution up to 4096x2304 @ 60Hz
- HDMI 2.0b: resolution up to 4096x2160 @ 60Hz
- VGA: resolution up to 1920x1200 @ 60Hz

### Ethernet

- 1x Intel® i225LM 2.5 Gigabit Ethernet Controller, supports vPro
- 2x Intel® i225LM/i225V 2.5 Gigabit Ethernet Controller

### Storage / Drive Bays / Slots

- 3x 3.5"
- 1x 5.25" (optional pre-assembled with DVDRW)
- 1x 2260/2280/22110 M.2 M-Key (PCIe x4 Gen4), supports SSD
- 1x 2230 M.2 E-Key (supports CNVi)
- 1x 3042/3052 M.2 B-Key (supports 4G/5G/LTE)

### RAID / SATA

- 8x SATA 3.0 (Support RAID 0/1/5/10)

### Expansion Slots

- 2x PCIe x16 Gen 4 (1 x16 signal or 2 x8 signal)
- 2x PCIe x4 Gen 4
- 1x PCIe x4 Gen 3
- 2x PCI 32-bit/33 MHz

### Front I/O

- 2x USB 2.0

### Rear I/O

- 1x DP, 1x HDMI, 1x VGA, 3x RJ45 LAN, 2x DB9 RS232/422/485
- 5x USB 3.2 Gen2, 1x USB 3.2 Gen2x2 Type-C, Line-in/out, Mic-in

### Other Internal Connectors / Functions

- 4x RS232, 2x USB 2.0, 2x USB 3.2 Gen1, 1x Thunderbolt header
- 1x 16-bit GPIO, TPM 2.0, 1x PS/2 header

### Power Supply

- Power input: 550W Redundant PSU, 100-240V AC 50~60 Hz

### Cooling

- 2x 80mm, 2x 60mm Cooler

### Mechanical

- Heavy Duty Cold Rolled Electroplated Steel
- Mounting: optional slide-rails
- Power / Reset Button in front

### Dimensions

- Dimension (W x H x D mm): 483 x 133 x 400 mm
- Weight: 17 kg

### Environment

- Operating Temperature: 0°C to 50°C
- Storage Temperature: -20°C to 70°C
- Humidity: 10 ~ 90%, non-condensing

### Certifications

- CE

### Operating System Support

- Windows 10 Pro / 10 IoT LTSC / Windows 11

### Ordering Information

#iROBO-3042A-5142