


# ASMB-782

## LGA 1155 Intel® Xeon® E3/ E3 v2/ 2nd and 3rd Generation Core™ ATX Server Board with 2 PCIe x16 slots (x8 link), 2 PCIe x4, USB 3.0, Quad LANs



- LGA 1155 Intel® Xeon® E3 / E3 v2 / 2nd and 3rd Generation Core™ i3 / Pentium processors
- DDR3 1600 MHz ECC UDIMM up to 32GB
- Two PCIe x16 slots (x8 link) and two PCIe x4 slots
- Quad LANs with teaming function
- Four USB 3.0 ports

**Software APIs:** SMBus H/W Monitor Watchdog


**Utilities:** Monitoring



### Specifications

Form Factor	ATX form factor						
Processor System	Socket	Intel LGA 1155					
	CPU type	Intel Xeon E3-1200/E3-1200 v2/ 2nd and 3rd Generation Core i3/i5/i7 / Pentium and Celeron series					
Core Logic	Chipset	Intel C216 chipset					
Memory	Total slots	4 (Dual Channel)					
	Max. capacity	32 GB					
	Memory type	DDR3 ECC/Non-ECC 1600/1333/1600 MHz UDIMM (240-pin)*					
	Memory size	1 GB, 2 GB, 4 GB, 8 GB					
Expansion Slots	Total PCI/PCI-X/PCIe slots	7					
	Slot location 1	PCI					
	Slot location 2	PCIe x4 (Gen2 x4 link)					
	Slot location 3	PCI					
	Slot location 4	PCI					
	Slot location 5	PCIe x16 slot (Gen3 x8 link)					
	Slot location 6	PCIe x16 slot (Gen3 x8 link)					
Graphics	Controller	Intel HD Graphics 2500/P3000/P4000					
	VRAM	1 GB maximum shared memory with 2 GB and above system memory installed					
Storage	SATA controller	Intel C216: 4 SATA2 3 Gb/s ports, 2 SATA3 6Gb/s Intel Matrix Storage (for Windows only) (Supports software RAID 0, 1, 10 & 5)					
	SAS controller	-					
Networking	Interface	10/100/1000 Mbps					
	Controller	GbE LAN1: Intel 82579LM; GbE LAN2/3/4: Intel 82574L					
	Connector	RJ-45 x 4 for G4 version					
Onboard I/O Connectors	PSU connector	24-pin SSI power connector + 8-pin SSI 12 V power connector					
	USB connector	2 USB 3.0; 8 USB 2.0(2 x USB Type-A)					
	Fan header	5 (4-pin)					
	SMBus	2					
	Chassis intruder	1					
	Front LAN LED	2					
	Serial port header	1 (RS-232)					
	Audio Connector	1 (Realtek ALC 892 optional)					
	DVI Connector	1 for optional DVI-D output					
Rear I/O Connectors	External serial port	1 (RS-232)					
	External USB port	4 (2 USB 3.0 and 2 USB 2.0)					
	VGA port	1					
	RJ-45	2 for G2 version, 4 for G4 version					
	PS/2 KB/mouse	2					
Watchdog Timer	Output	System reset					
	Interval	Programmable 1 ~ 255 sec					
Power Requirement	Power On	3.3V	5V	12V	12V_8P	5 Vsb	-V12
		4.69A	1.39A	0.4A	3.01A	1.95A	0.01A
Environment	Temperature	Operating				Non-operating	
		0 ~ 60° C (32 ~ 140° F) Depends on CPU speed and cooler solution				-40 ~ 85° C (-40 ~ 185° F)	
		Humidity				5% ~ 95% (Non-condensing)	
Physical Characteristics	Dimensions	304.8 x 244 mm (12" x 9.6")					

\*DDR3 1600 is only supported by Xeon E3 v2, Core i3 3xxx and Pentium G2xxx series processors.



## Ordering Information

Part Number	Chipset	Memory	LAN	USB 3.0
ASMB-782G2-00A1E	C216	DDR3 ECC UNB/Non-ECC	2	4
ASMB-782G4-00A1E	C216	DDR3 ECC UNB/Non-ECC	4	4

## Packing List

Part Number	Description	Quantity
2066S78200	Driver CD	x 1
2006S78210	Startup manual	x 1
1700003194	SATA data cables	x 2
1700022749-11	SATA power cables	x 2
1960052312T000	I/O shield	x 1

## Optional Accessories

Part Number	Description
1700002204	Dual port USB 2.0 cable (27 cm) with bracket
1700008461	Four port USB 2.0 cable (30.5 cm) with bracket
1960052651N021	LGA 1151/1150/1155 CPU cooler for 2U/4U and wallmount chassis
1960049408N001	LGA 1151/1150/1155 1U CPU Cooler
1700008809	Printer port cable kit (25 cm)
1700020294-01	Printer port cable kit (42 cm)
1701090401	COM port cable with bracket (40 cm)
1700008822	DVI cable with bracket
1700020277-01	Dual port USB 3.0 cable with bracket (30 cm)
AIMB-AUDIO-HDA1E	HD Audio-Card
1920000406T000	1U I/O shield
PCA-TPM-00A1E	TPM Module with Infineon TPM 1.2 solution

## I/O View



ASMB-782G4-00A1E

ASMB-782G2-00A1E

Note 1: Please order 1 piece of each 1960049408N001 and 1920000406T000 for configuring ASMB-782 with 1U chassis.

Note 2: Purchasing ASMB-782's proprietary CPU cooler from Advantech is a must. Other brands' CPU coolers are NOT compatible with ASMB-782.