

ORION-D3502P

350W ATX mini-redundant
with active PFC power supply



SPECIFICATION

Input Voltage	100V~240V AC
Input Frequency	47 ~ 63 Hz
Input Current	6A@115V, 3A@230V
Efficiency	> 80%
Holdup Time	16 ms. at full load
Over Voltage Protection	3.3@4.5V; 5V@6.5V; 12V@14.5V
MTBF	> 100,000 hrs
EMI & Safety Approval	UL, cUL, TUV, CE, FCC
Temperature/Humidity	Operating: 0 ~ 40°C, 20 ~ 90%RH Storage: -20 ~ 60°C, 5 ~ 95%RH
Dimension (WxDxH)	150 x 190 x 84 mm; 5.9" x 7.2 x 3.4"

FEATURES

- Mini-redundant ATX power supply suitable for 2U and larger chassis
- 350W output
- Active PFC, full-range input

ORDERING GUIDE

- **ORION-D3502P**
350W PS/2, w/active PFC, ATX power supply

DC OUTPUT

	+5V	+3.3V	+12V	-5V	-12V	+5Vsb
Max. Load	20A	20A	18A	0.5A	0.8A	2A
Min. Load	0.5A	0.5A	0.5A	0A	0A	0A
Load Reg.	±5%	±5%	±5%	±10%	±5%	±5%
Cross Reg.	±5%	±5%	±5%	±10%	±5%	±5%
Line Reg.	±1%	±1%	±1%	±1%	±1%	±1%
Ripple	50mv	50mv	20mv	20mv	200mv	50mv
Noise	50mv	50mv	120mv	200mv	200mv	50mv