


**6GK6022-0MS2.-.... M2200**

Technical Data

<b>Product-type designation</b>	<b>RUGGEDCOM M2200</b>
<b>Product description</b>	<p><b>MIL-STD 9-Port Managed Gigabit Ethernet Switch, 128-bit Encryption</b></p> <p>THE RUGGEDCOM M2200 IS A MIL-STD HARDENED, FULLY MANAGED, MODULAR GIGABIT ETHERNET SWITCH; 128-BIT ENCRYPTION; UP TO 9-GIGABIT ETHERNET PORTS COPPER AND/OR FIBER; 2 PORT MODULES FOR TREMENDOUS FLEXIBILITY; SUPPORTS MULTIMODE AND SINGLEMODE FIBER; NON-BLOCKING, STORE AND FORWARD SWITCHING; SUPPORTS LC CONNECTORS FOR FIBER, MICRO-D CONNECTORS FOR COPPER</p>
	
<b>Transmission rate</b>	
Transfer rate / 1	10 Mbit/s
Transfer rate / 2	100 Mbit/s
Transfer rate / 3	1000 Mbit/s
<b>Interfaces</b>	
Number of electrical/optical connections / for network components or terminal equipment / maximum	9
<ul style="list-style-type: none"> <li>remark</li> </ul>	Slot 1, 2, 3, 4, with 2 Ports each + Slot 5 with 1 Port
number of electrical/optical connections / for gigabit Ethernet / maximum	9
Number of electrical connections	
<ul style="list-style-type: none"> <li>for network components and terminal equipment</li> <li>maximum</li> <li>for gigabit Ethernet / maximum</li> <li>for operator console</li> <li>for management purposes</li> </ul>	<p>9</p> <p>9</p> <p>1</p> <p>0</p>
Design of electrical connection	
<ul style="list-style-type: none"> <li>for operator console</li> <li>for power supply and signaling contact</li> </ul>	<p>RJ45</p> <p>10-pole terminal block, screwable or plugable, screw contact</p>
Number of optical connections / for network components or terminal equipment / maximum	9

operating distance / of optical interface / depending of used optical fiber / at gigabit	0.5...25 km
<b>Signal-Inputs/outputs</b>	
Relay design	Form-C contact relay (SP CO) as critical alarm relay
type of the relay output	Change-over (NO/NC)
operating voltage / of the signal contact	
<ul style="list-style-type: none"> <li>at AC</li> <li>maximum</li> </ul>	250 V
<ul style="list-style-type: none"> <li>at DC</li> <li>maximum</li> </ul>	125 V
Operating current / of signaling contacts	
<ul style="list-style-type: none"> <li>at AC</li> <li>at 250 V / maximum</li> </ul>	2 A
<ul style="list-style-type: none"> <li>at DC</li> <li>at 30 V / maximum</li> </ul>	2 A
<b>Supply voltage, current consumption, power loss</b>	
product options / wide range power supply	Yes
<b>Type of voltage / 1 / of the supply voltage</b>	DC
Supply voltage / 1	
<ul style="list-style-type: none"> <li>rated value</li> <li>rated value</li> </ul>	24 V
	10...36 V
Current consumed / 1 / at rated value of supply voltage / max.	1.2 A
<b>Type of voltage / 2 / of the supply voltage</b>	DC
Supply voltage / 2	
<ul style="list-style-type: none"> <li>rated value</li> <li>rated value</li> </ul>	48 V
	36...59 V
Current consumed / 2 / at rated value of supply voltage / max.	0.6 A
<b>Type of voltage / 3 / of the supply voltage</b>	DC
Supply voltage / 3	
<ul style="list-style-type: none"> <li>rated value</li> </ul>	88...300 V
<b>Type of voltage / 4 / of the supply voltage</b>	AC
Supply voltage / 4	
<ul style="list-style-type: none"> <li>rated value</li> </ul>	85...264 V
Power loss	
<ul style="list-style-type: none"> <li>maximum</li> </ul>	28 W
<b>Permitted ambient conditions</b>	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operating</li> <li>Comment</li> </ul>	-40...+85 °C
	A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
Coating	Conformal Coating optional
operating condition / fanless operation	Yes
Protection class IP	IP40

Design, dimensions and weight	
design of display/ LED panel mounted on the front or on the rear side	Yes
Design	19" rack
number of height rack units / related to 19 inch cabinet	1
Number of slots	5
Width	464.8 mm ( 18.3 in )
Height	44.2 mm ( 1.74 in )
Depth	315 mm ( 12.4 in )
Net weight	4.8 kg
Material / of the enclosure	18 AWG galvanized steel enclosure
Type of mounting	
<ul style="list-style-type: none"> <li>• Installation 19 inch</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	Yes
Product properties, functions, components / general	
number of automatically learnable MAC addresses	8192
memory capacity	
<ul style="list-style-type: none"> <li>• of MAC-address table</li> </ul>	64 Kibyte
<ul style="list-style-type: none"> <li>• of message buffer / maximum</li> </ul>	2 Mibyte
switch-latency period	7 $\mu$ s
transfer rate / of the switch	18 Gbit/s
number of priority channels	5
product characteristic	
<ul style="list-style-type: none"> <li>• no head-off-line-blocking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Switching-Method Store &amp; Forward</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Zero-Packet-Loss technology</li> </ul>	Yes
Product functions / management, configuration	
Product function	
<ul style="list-style-type: none"> <li>• CLI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• web-based management</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MIB support</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RMON</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• switch-managed</li> </ul>	Yes
Protocol / is supported	
<ul style="list-style-type: none"> <li>• Telnet</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTPS</li> </ul>	No
<ul style="list-style-type: none"> <li>• TFTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IGMP (snooping/querier)</li> </ul>	Yes
number of groups / at IGMP	256
Protocol / is supported	
<ul style="list-style-type: none"> <li>• SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2</li> </ul>	No
<ul style="list-style-type: none"> <li>• SNMP v2c</li> </ul>	Yes

<ul style="list-style-type: none"> <li>• SNMP v3</li> </ul>	Yes
product function / for MIB-support	
<ul style="list-style-type: none"> <li>• by BRIDGE-MIB</li> </ul>	RFC1493
<ul style="list-style-type: none"> <li>• by IF-MIB</li> </ul>	RFC2863
<ul style="list-style-type: none"> <li>• by RMON-MIB</li> </ul>	RFC2819
<ul style="list-style-type: none"> <li>• by RSTP-MIB</li> </ul>	draft-ietf-bridge-bridgemib-smiv2-03-RSTP-MIB
<ul style="list-style-type: none"> <li>• by SNMPv2-MIB</li> </ul>	RFC1907
<ul style="list-style-type: none"> <li>• by SNMPv2-SMI</li> </ul>	RFC2578
<ul style="list-style-type: none"> <li>• by SNMPv2-TC</li> </ul>	RFC2579
<ul style="list-style-type: none"> <li>• by TCP-MIB</li> </ul>	RFC2012
<ul style="list-style-type: none"> <li>• by UDP-MIB</li> </ul>	RFC2013
<b>Product functions / VLAN</b>	
Product function	
<ul style="list-style-type: none"> <li>• VLAN - port based</li> </ul>	Yes
Number of VLANs / maximum	255
VLAN-Identification number	1...4094
Protocol / is supported / GVRP	Yes
<b>Product functions / DHCP</b>	
Product function	
<ul style="list-style-type: none"> <li>• DHCP client</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP Option 82</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP Option 66</li> </ul>	No
<ul style="list-style-type: none"> <li>• DHCP Option 67</li> </ul>	No
<b>Product functions / Routing</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• PPP</li> </ul>	Yes
<b>Product functions / Redundancy</b>	
Product function	
<ul style="list-style-type: none"> <li>• redundancy procedure STP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RSTP redundancy protocol</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• redundancy procedure MSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• eRSTP</li> </ul>	Yes
Protocol / is supported	
<ul style="list-style-type: none"> <li>• STP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MSTP</li> </ul>	Yes
<b>Product functions / Security</b>	
product function	
<ul style="list-style-type: none"> <li>• IEEE 802.1x (radius)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RADIUS client</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• RADIUS</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TACACS+</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SSL</li> </ul>	Yes
key length	

• at SSL	128 bit
• at RSA	1024 bit
product function / port-rate-limiting	Yes
<b>Product functions / Time</b>	
product function	
• SNTP-client	Yes
• SNTP-server	Yes
Protocol / is supported	
• SNTP	Yes
<b>Standards, specifications, approvals</b>	
Standard	
• for EMC	FCC Part 15 (Class A), EN55022 (CISPR22 Class A)
• for safety / of CSA and UL	cCSAus (Compliant with CSA C22.2 No. 60950, UL 60950, EN60950) (Pending)
Laser protection class	Complies with 21 CFR Chapter1, Subchapter J
Verification of suitability	
• CE mark	Yes
• IEC 61850-3	Yes
product conformity	
• according to IEEE 802.3-10BaseT	Yes
• according to IEEE 802.3u-100BaseTX	Yes
• according to IEEE 802.3u-100BaseFX	Yes
• according to IEEE 802.3x-Flow Control	Yes
• according to IEEE 802.3ab-1000BaseT	Yes
• according to IEEE 802.3ad-Link Aggregation	Yes
• according to IEEE 802.1d-MAC Bridges	Yes
• according to IEEE 802.1d-STP	Yes
• according to IEEE 802.1p-class of service	Yes
• according to IEEE 802.1Q-VLAN tagging	Yes
• according to IEEE 802.1Q-2005 (formerly IEEE 802.1s) MSTP	Yes
• according to IEEE 802.1w-RRST	Yes
• according to IEEE 802.1x-port based Network Access Control	Yes
product conformity	
• according to MIL-STD 167-Vibration	Yes
• according to MIL-STD 461-EMI	Yes
• according to MIL-STD 810-Temperature and Humidity	Yes
• according to MIL-S 901D-Shock (Hard Mounted)	Yes
• according to MIL-STD 1399 Magnetic Field (DC Magnetic Exposure)	Yes
product conformity	
	Yes

- RFC768-UDP
- RFC783-TFTP
- RFC791-IP
- RFC792-ICMP
- RFC793-TCP
- RFC826-ARP
- RFC854-Telnet
- RFC894-IP over Ethernet
- RFC1112-IGMPv1
- RFC1519-CIDR
- RFC1541-DHCP (client)
- RFC2030-SNTP
- RFC2068-HTTP
- RFC2236-IGMPv2
- RFC2284-EAP
- RFC2475-Differentiated Service
- RFC2865-RADIUS
- RFC3414-SNMPv3-USM
- RFC3415-SNMPv3-VACM

Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes

#### Further Information / Internet Links

##### Internet link

- to website
- Industry Mall/RUGGEDCOM Selector <http://ruggedcom-selector.automation.siemens.com>
- Siemens RUGGEDCOM <http://siemens.com/ruggedcom>
- Industry Mall <http://www.siemens.com/industrial-controls/mall>
- selection instrument cables and connectors <http://www.siemens.com/snst>
- CAx-Download-Manager <http://www.siemens.com/cax>
- industrial communication <http://www.siemens.com/simatic-net>
- Information und Download Center <http://www.siemens.com/automation/net/catalog>
- image database <http://automation.siemens.com/bilddb>
- Industry Online Support <http://support.automation.siemens.com>

**letzte Änderung:**

Feb 24, 2014