

iROBO-MC156P-FS3-WDC

15.6" Galvanized steel Wall Mount Display



Features

- 15.6" TFT-LCD 16:9 Panel PC
- Full HD Resolution
- High Brightness available
- 3 Years Warranty

Specifications

Display

- LED Size: 15.6" 16:9
- Resolution: 1920 x 1080
- Brightness: 1500 cd/m² (optional 1000 / 500 cd/m²)
- Contrast Ratio: 1000:1
- Colors: 16.7 M
- Viewing Angle (H/V°): 178 / 178
- Display Area: 344.2 x 193.5 mm
- Screen Diagonal: 394.8 mm
- Backlight: LED
- Backlight MTBF (hrs): 50000
- Response Time: 25 ms

Touch Screen

- 10 points Multi-touch, Support Active Stylus, USB interface
- Hardness of touch glass 7H, Anti-glare Surface

OSD Function

- OSD keys on rear side

Audio

- Line in 3.5 mm jack, 2x 2W Speakers

Rear I/O

- 1x VGA
- 1x HDMI
- 1x DP
- 1x USB
- Power input terminal block

Power Supply

- Power input: +9~+36V DC

Mechanical

- Galvanized Steel (SECC)
- IP front protection: no
- Mounting: Wall mount VESA 75x 75 / 100x100 mm

Dimensions

- Dimension (W x H x D mm): 385 x 240 x 41 mm
- Weight: 3.3 kg Net / 5.8 kg Gross

System & Environment

- Operating temperature: -20°C to 70°C
- Storage temperature: -20°C to 70°C

Certifications

- CE

Optional Features

- Auto Dimming with Light Sensor
- IP65 Front protection
- Open-frame Brackets (57333200 ACS-MC-OPENFR-BRK1)
- Anti-Glare Surface Treatment
- Antibacterial (AB Film)
- Anti-Glare +UV-Cut (AG+UV Film)
- Anti-Glare +Fouling/Fingerprint (AG+AFP Film)
- Anti-Reflective +Fouling/Fingerprint (AR+AFP Film)
- AG+AR+AFP Film

Ordering Information

iROBO-MC156P-FS3-WDC (P/N: 57332900)

Package Contents:

- 1x VGA Cable D-SUB 15-pin 1.2 M
- 1x USB Touch Cable 1.5M