

10.4" Vehicle Mounted Computer w/Defroster FM10-HT

Product Features:

- Field replaceable front panel to reduce service cost and prevent productivity loss
- High Performance Intel ATOM platform (E3845 2M Cache, 1.91GHz)
- Support Windows 10 IoT Enterprise, Windows Embedded 8.1 Industry Pro, Windows 7 Professional for Embedded system, or Windows Embedded Standard 7
- Magnesium Alloy Housing
- Anti-scratch resistive touch
- SMA Connector for external antenna
- Fan-Less & Robust Design
- Wide range Operating Temperature
- Built-in Defroster
- Carrier Approval: PTCRB, AT&T

Product Specifications:

System Specification	Processor	Intel Quad-Core Atom E3845 Processors (1.91GHz)
	System Memory	4GB SODIMM DDR3L-1600 (up to 8GB)
	Storage	64GB M.2 MLC SSD (up to 256 GB)
	Operating System	Windows 10 IoT Enterprise Windows Embedded 8.1 Industry Pro Windows 7 Professional for Embedded system Windows Embedded Standard 7
Display Specification	Size / Technology	10.4" (4:3)
	Resolution	1024*768
	Viewing angle	-88~88(H) ; -88~88(V)
	Brightness	400 nits
	Touch	Anti scratch Resistive touch and support for finger touch and stylus
Wireless Communication	WLAN	802.11 a/b/g/n/ac
	Bluetooth	Bluetooth 4.0
	GPS	Optional u-blox NEO-6Q (located at the vehicle dock)
	WWAN	Optional 4G (LTE,HSPA+,GSM/GPRS/EDGE,EV-DO Rev A, 1xRTT) Optional 3G (HSPA+,GSM/GPRS/EDGE)
	Carrier Approval	PTCRB, AT&T
Data Capture	Camera	2MP Camera at front side (only available on Windows 7/ 8.1/ 10 IoT)
Mechanical and Environment	Dimension (W x L x H)	Computer: 268 x 214 x 35 mm (10.6" x 8.42" x 1.37") Docking: 202 x 245 x 52 mm (7.9" x 9.6" x 2.04")
	Housing	Magnesium Alloy housing with fanless design
	Weight	Computer 1.7kg and Docking 1.6kg
	Operating Temperature	-30°C to 50°C (-22° to 122° F)
	Storage Temperature	-30°C to 60°C (-22° to 140°F)
	Humidity	5% to 95% RH, non-condensing
	IP Proof	IP65
	Impact	Support EN62262 IK70 rating
	Shock	Compliant with MIL-STD-810G Method 516.6 Procedure I
	Vibration	Compliant with MIL-STD-810G Method 514.6 Procedure I
	Certifications	CE, FCC, UL60950-1, EN60950-1, PTCRB, FCC (Electromagnetic Emissions), IC (ICES-003)
I/O Connectors	Computer	1 x SIM Card Slot , 1 x SD Card Slot , 1 x USB 3.0, 1 x 12V DC in power input jack
	Dock	1 x COM 1, 1 x COM 2, 1 x USB 2.0 port (support 2 x USB 2.0), 1 x CANBUS / AUDIO, 1 x 400Mbps LAN port (Optional PoE) as a Power sourcing equipment (PSE) support 802.3at Type 2, 1 x Power Connector, SMA Connector(female) for external antenna (WiFi, GPS, WWAN(optional))
Mobile Device Management	Mobile Device Management	SOTI MobiControl compatible
Power Management	Power Input	10V-60V with isolation power and ignition control
	UPS Battery	7.6V typ. 3800mAh Li-Polymer Battery (2S1P)

Renderings :



FM10-HT

FM10C-HT (Computer)

FMVD (Dock)

10.4" Vehicle Mounted Computer w/Defroster

FM10-HT

Docking Features:

- Wide range power (10V~60V) & Ignition control
- Smart Docking Design
- u-blox NEO-6Q GPS (Optional)
- High power speaker (3W * 2)
- With LED Reading Light
- Release latch and Key Lock to secure the device
- Power switch, to give power to the device
- VESA 75, 100, and RAM Mount



FM10 – Accessories

Package Contents

Before using this Vehicle Mounted Computer, please make sure that all the items listed below are present in your package:

Computer - FM10 98P010A000J7	Dock + latch locking key 98D000A00003	5 m Power Cable with fuse kit 98K000A0006O	0.3 m USB Cable 9483098080K0	External Antenna Fixing Bracket 88111T201203	Cable Clamp Kit 98K000A0005W
WiFi External Antenna x 2 39700000000G	Quick Start Guide 9152111100S	Driver CD 9171111101R	0.15m power converter cable 94J602G030K2	84W Adapter with power cable 922D084W12V1	

Optional Accessories

3 m DC Jack Power Cable 94J0086020K0	1.2 M 120 Watt Adapter (For Heater Model) 90PO12120005	4.2 m Adapter with power cable 98K000A0006L	1.8 m RS232 Cable 94G3094090K2	0.3 m Audio Cable 94E215R060K0	1.8 m CAN BUS Y Cable 94E2150090K0
2 m IP65 LAN Cable 94I0080080KF	WWAN External Antenna x 2 39700000000H	15A, 250V, VDA type Fuses 94JL01L01000	Spare Key for Vehicle Dock 9B000000007N	DC12V/2A Input UHF Fixed Reader 9BRFID000012	Mounting kit 1 – No Drill 98K000A0005Y
Mounting kit 2 – Drill 98K000A0006P	Mounting kit 3 – Keyboard Mounting 98K000A0005X	GPS & LTE 2M Combo Antenna (VM240) 39700000000M	GPS & LTE 5M Combo Antenna (VM9C) 39700000000N	GPS & LTE & Wi-Fi Magnetic Combo Antenna (VM10S) 39700000000U	Stylus kit + Screw 98K000A0005T