

# Gladius 10

## 10.1" Rugged Android™ Handheld Device with Octa-core Processor



### Features

- MTK MT8392 Octa-core Cortex™A7 processor, Android-based
- Fully rugged for warehousing / transportation / medical / mPOS applications
- 10.1" TFT color LCD display
- 5-point Projected Capacitive Multi-Touch
- Wi-Fi, Bluetooth, 3G and GPS supported
- Built-in 1D/2D barcode scanner and NFC reader
- Operating temperature: -10 ~ 50°C
- IP-65 certified, 1.2m (4ft.) drop resistance

### Durability Features

IP-65 certified  
 1.2m (4ft.) drop-resistance (with rubber tube)  
 Raised bezel for LCD impact protection  
 I/O ports with hinged rubber covers

### System

CPU MTK MT8392 Octa-core Cortex™A7 1.7GHz  
 OS Android™ v4.4  
 Memory 2GB  
 Storage 16GB  
 Audio Integrated microphone  
 Integrated speaker  
 1 x 3.5mm stereo headphone jack

### Peripherals and Devices

Camera Front: 5.0 megapixel camera  
 Rear: 13.0 megapixel AF camera with flash  
 Accelerometer (G-sensor)  
 Sensor Gyroscope  
 Barometer  
 NFC ISO/ IEC 14443 TypeA, TypeB ; ISO/ IEC 15693  
 WLAN Integrated IEEE 802.11 b/g/n  
 Wi-Fi certified Miracast™  
 Bluetooth Integrated Bluetooth 4.0 LE + EDR class 2,  
 with HID, A2DP, AVRCP, BIP, BPP, FTP, HFP, HSP,  
 OPP, SPP supported  
 WWAN 3G HSPA+(21/5.76 Mbps), GPRS, EDGE  
 Navigation GPS, AGPS & E-compass  
 Barcode Scanner 1D/2D barcode scanner with physical trigger button  
 (optional)

### I/O Interface

USB Port 1 x Micro USB 2.0 port  
 SD Slot 1 x microSD/SDHC card slot  
 SIM Socket 2 x SIM card slots  
 HDMI 1 x Mini HDMI port

### LCD Display

Size/Type 10.1" TFT LCD  
 Resolution 1280 x 800

### Touch Screen

Type 5-point Projected Capacitive Touch screen

### Power Supply

Power System External AC power adapter  
 Battery Type Lithium-ion rechargeable battery  
 Customer replaceable (for maintenance)  
 Battery Capacity 3.8V, 9300mAh, 35.34Whr  
 Battery Life Up to 8 hours battery life with the normal operation  
 Adapter Input Input: AC100~240C, 50~60 Hz  
 Adapter Output DC power output: 5V/2A


### Mechanical & Environmental

Operating Temp. -10°C ~ 50°C (14°F ~ 122°F )  
 Storage Temp. -20°C ~ 75°C (-4°F ~ 167°F)  
 Operating Humidity 95% (non-condensing)  
 Dimensions 278.4 x 190.7 x 22.9 mm  
 (W x H x D)  
 (10.96" x 7.51" x 0.90")  
 Weight 1035g (2.29lb) (with battery)

### Ordering Information

GT1000 10.1" Android™ Rugged IoT Handheld Device with  
 Octa-core Processor and Front & Rear Camera  
 GT1000-2D 10.1" Android™ Rugged IoT Handheld Device with  
 Octa-core Processor, Front & Rear Camera and  
 1D/2D Barcode Scanner

## Dimensions



---

## Standard Accessories

Micro USB cable



Rechargeable Li-ion battery pack



Earphone



User Manual



---

## Optional Accessories

Universal power adapter

